Survitec AFFF 1% F-25 PD4142

FOAM CONCENTRATE

Survitec Foam concentrates are either fluoroprotein or synthetic foam types. Depending on application, it can be alcohol resistant for polar. Solvent fi res or regular ones for hydrocarbon fi res. Foam concentrates offered are MED, IMO MSC.1/Circ.1312 approved. Some foam concentrates are HOCNF and ICAO approved.

FEATURES

- CLASS B FIRES
- FOR FIRES IN HYDROCARBONS
- OUR AFFF 1% F-25 MEETS THE LATEST IMO REGULATIONS MAKING IT IDEAL FOR UPDATING YOUR VESSELS' FOAM FIREFIGHTING SYSTEM
- IDEAL FOR USE FOR YOUR OIL TANKERS' AND HELIDECKS' FOAM SYSTEMS
- WHEN STORED CORRECTLY IN ACCORDANCE WITH THE MANUFACTURER'S GUIDELINES OR IN THE CONTAINERS IT IS SUPPLIED IN, IT WILL GENERALLY HAVE A SHELF LIFE IN EXCESS OF 10 YEARS
- GLOBAL AVAILABILITY, FLEET FLEXIBILITY AND STANDARDISATION MAKE IT IDEAL FOR A LONG-TERM SOLUTION



TECHNICAL DATA					
Туре	Synthetic AFFF				
Usage	Monitors and Portable Applicators				
Pump	Centrifugal				
Density kg/L @ 20°C	1.06 ± 0.02				
Viscosity +20 °C (IMO 3.4) mm²/s	< 20				
Viscosity 0°C (IMO 3.4) mm²/s	< 50				
Viscosity -15 °C (IMO 3.4) mm²/s	< 200				
pH at 20 °C	6.5 - 8.5				
Storage temperature	-25 °C to + 50 °C				
Freezing Point	-20 °C				
Sediments, Max (% Vol)	None				
Sediments By Aging, Max at -25 °C	< 0.25				
Sediments By Aging, Max at +60 °C	< 0.25				
Expansion	Low				
Expansion Ratio	15 times				
Drainage time 25%	2-4 min				
Drainage In Time 50 %	4-8 min				

Ordering Information

Product Number	Product Name
777696	AFFF 1 % F-25 Foam Concentrate 20 L Can
777695	AFFF 1 % F-25 Foam Concentrate 200 L Drum

Approvals

Approved to IMO MSC.1/Circ.1312, MED/3.58.



FOAMS ON REQUEST										
Products		Product	Approvals	Can	Drum	Foam Top-up	Replacement Foam	Can	Drum	
AFFF	1%	AFFF1% F-15 PD4141	MED/DNV/ICAO	777690	777690	STHAMEX AFFF 1% F-25 PD4142	AFFF 1% F	777696	777695	

SUPERSEEDED FOAMS

Products		Product	Approvals	Can	Drum	Foam Top-up	Replacement Foam	Can	Drum
AFFF	1%	UNIRAL 1	Not Available	677211	677187	Not Available	AFFF 1% F	777696	777695



GET IN TOUCH