Survitec ABC POWDER STORED PRESSURE FIRE EXTINGUISHER

Survitec's range of fire extinguishers offers you higher fire ratings, easier fire fighting capability and increased levels of user safety. Whether you require cartridge, stored pressure or wheeled we use high grade quality materials and coatings giving your extinguisher longer life

FEATURES

and reduced maintenance costs.

- OUR FIRE EXTINGUISHERS BOAST HIGH LEVELS OF MONO AMMONIUM PHOSPHATE GIVING YOU QUICKER FIREFIGHTING CAPABILITY EVEN ON ELECTRICAL FIRES UP TO 35 KV
- HIGH FIREFIGHTING CAPABILITIES MEANING QUICKER
 AND SAFER FIRE FIGHTING
- LONG LIFE AND LOW MAINTENANCE COSTS ARE ASSURED AS OUR EXTINGUISHERS ARE MANUFACTURED FROM 2 MM THICK STEEL, SHOT BLASTED, POLYESTER COATED AND WITH AN ANTI-RUST SAFETY PIN



ABC POWDER STORED PRESSURE

FIRE EXTINGUISHER

Accessories

Product Number	Product Name
671909	6 kg Fire Extinguisher Bracket with Strap
739516	9 kg Fire Extinguisher Bracket with Strap
743112	12 kg Fire Extinguisher Bracket with Strap
756387	12 kg Fire Extinguisher Bracket with Strap 5 pack

Ordering Information

Product Number	Product Name
766995	ABC Stored Pressure Fire Extinguisher 2 kg with bracket PP2P
671594	ABC Stored Pressure Fire Extinguisher 6 kg without bracket PP6P
739508	ABC Stored Pressure Fire Extinguisher 9 kg without bracket PP9P
743104	ABC Stored Pressure Fire Extinguisher 12 kg without bracket PP12P

TECHNICAL DATA						
Capacity	2 kg	6 kg	9 kg	12 kg		
Bracket	Yes	No	No	No		
Minimum Discharge Range	3 m	4.5 m	4.5 m	4.5 m		
Test Pressure	27 bar	24 bar	24 bar	24 bar		
Working Pressure	13 bar (20 °C)	13.5 bar	13.5 bar	13.5 bar		
Weight Empty	2.1 kg	3.3 kg	4.4 kg	4.8 kg		
Weight Full	4.1 kg	9.4 kg	13.5 kg	16.9kg		
Height	380 mm	530 mm	597 mm	630 mm		
Diameter	110 mm	150 mm	180 mm	190 mm		
Fire Rating	13A-89B-C	27A - 144B - C	43A-233B-C	55A-233B-C		
Operating Temperature Range	-20 °C to +60 °C					

Instructions For Use

- 1. Pull out the safety pin by pulling the ring
- 2. Press the trigger and steam the jet at the base of the flames

.....

Operation

After removing the safety pin, press the control lever, releasing the powder. A check valve inside the head cap controls the flow rate. The fact that the fire extinguisher is so simple to use means that risks of incorrect use are greatly reduced.

Stored Pressure Extinguisher

The extinguisher is pressurised during manufacture and undergoes a helium test to ensure it is totally leak tight and an indicator then monitors the pressure over time. The extinguisher must be returned to the factory for refilling; in practice on-site requalification involves exchanging the extinguisher

ABC POWDER STORED PRESSURE

FIRE EXTINGUISHER

Spare Stored Pressure Extinguisher Regulations

For fire extinguishers which cannot be recharged on board, additional portable fire extinguishers of the same quantity, type, capacity and number must be provided for 100% of the first ten extinguishers and 50% of the remaining fire extinguishers. Not more than sixty total spare extinguishers are required.

Approvals

These fire extinguisher hold Apragaz notified body EC type examination certificate in accordance with Module B of the Maritime Equipment Directive 96/98 EC as amended (MED/3.2 Portable stored pressure fire extinguishers)

These extinguishers comply with European testing standards: EN 3-7



SETTING THE GLOBAL STANDARD FOR OVER 160 YEARS

Protecting over 1 million lives across the globe every day, our critical safety and survival solutions help marine, aviation, offshore, and defence personnel get home safely if the worst happens.

Taking responsibility for the entire product lifecycle – from precision engineering and R&D, to manufacturing and servicing – we never compromise when it comes to safety and survival. Committed to protecting lives, we know the small things matter.



GET IN TOUCH

Email info@survitecgroup.com