

EC TYPE EXAMINATION (MODULE B) CERTIFICATE No. MED010522CS/002

This is to certify that RINA Services S.p.A. (Notified Body No. 0474) did undertake the relevant type approval procedures for the equipment identified below, which was found to be in compliance with the Life-Saving appliances requirements of Marine Equipment Directive (MED) 2014/90/EU, including the requirements and testing standards of Regulation (EU) 2021/1158.

MED Item N°MED/1.1DescriptionLifebuoys

Type PERRYBUOY 4.0 KG

Applicant CAN-SB MARINE PLASTICS SRL

VIA L. IL MORO 27 46040 Casalmoro (MN)

ITALY

Testing standards IMO Res. MSC 81(70) as amended

Reference standards Reg. III/7, Reg.III/34 of SOLAS 74 as amended, IMO

Res.MSC.36(63)-(1994 HSC Code) 8, IMO Res MSC.48(66)-(LSA Code)

I,II, IMO Res.MSC.97(73)-(2000 HSC Code) 8.

Issued in Genoa on This Certificate is valid until January 20, 2022 January 19, 2027

This Certificate consists of this sheet plus an attachment

Giovanni Carratino

RINA Services S.p.A.



ATTACHMENT TO CERTIFICATE No. MED010522CS/002 Page 1 of 2

Manufacturer **CAN-SB MARINE PLASTICS SRL**

Place of Manufacturer VIA L. IL MORO 27 46040 Casalmoro (MN) **ITALY**

Product description

Outer diameter: 751 ± 2% Inner diameter: 450 ± 2%

Elliptical section: major axis 150 ± 7mm

minor axis 99 ± 7 mm

Thickness: 2 mm

Minimum weight of the lifebuoy: 4000 g

Materials: high density polyethylene RIGIDEX HD5502S

Buoyancy material: EUROPOL RCC 128P

Grabline made with a braid of high density polyethylene Ø 10 mm

Reference documents

Technical datasheet issued by CAN-SB MARINE Plastic and approved by RINA with n° CSST 10630; Main dimension drawing issued by CAN-SB MARINE Plastic and approved by RINA with n° CSST 10733.

Tests carried out

Test Report n° 2013/CS/01/2966 issued by RINA Laboratory and filed with n° CSST 10631

Test report n° 2013CS012966/RSA - Drop test from 60 mt witnessed and filed by RINA with n° CSST 10632

Field of application

Maximum installation height: 60 mt.

The lifebuoy is intended to operate the quick-release arrangement for the self-activated smoke signal and self-igniting light, attached to the lifebouy body.



ATTACHMENT TO CERTIFICATE No. MED010522CS/002 Page 2 of 2

The mark of conformity may only be affixed to the above type approved equipment and a Manufacturer's Declaration of Conformity issued when the production control phase module (D, E or F) of Annex II of the Directive is fully complied with a written inspection agreement with a Notified Body



"WHEELMARK FORMAT"

XXXX Notified Body number undertaking surveillance module

YYYY The year in which the mark is affixed

General conditions for the approval

- a) The initial conditions verified by RINA at the time of the approval are to be maintained
- b) Any changes to the initial conditions are to be promptly communicated to RINA, which reserves the right to repeat the relevant assessment
- c) This certificate will no be valid if the manufacturer makes any changes or modifications to the approved equipment, which have not been notified to, and agreed with RINA
- d) RINA personnel are to be allowed to witness during the performances of activities, upon their request
- e) The activities are to be carried out in compliance with the RINA Rules and/or other applicable Rules
- f) Should the specified regulations or standards be amended during the validity of this certificate, the product is to be reapproved prior to it being placed on board vessels to which the amended regulations or standards apply.