



WHEELED FOAM CARTRIDGE

FIRE EXTINGUISHER ↓

In high risk locations with limited access Survitec's range of wheeled extinguishers allow the user to fight fires from a longer distance giving protection from heat and fire. Wheeled extinguishers provide the ability to quickly move high capacity extinguishers closer to the fire easily.

Our foam portable fire extinguishers have a nozzle design that produce small individual droplets and not a jet. The droplets does not touch each other, which prevents electric current to be conducted. Because of this, they can be used on voltage up to 35kV with adequate training. In addition, these small droplets increase the energy absorption, making the extinguisher more efficient.

FEATURES

- **SPECIALLY BLENDED HIGH PERFORMANCE AFFF ADDITIVE ENABLES THE USER TO FIGHT FIRES QUICKLY AND EFFICIENTLY**
- **HIGH FIREFIGHTING CAPABILITIES MEANING QUICKER AND SAFER FIREFIGHTING**
- **LONG AND NON-KINKING HOSE WITH OPENING TAP GIVES DIRECT AND BETTER CONTROL TO FIGHT FIRES**
- **THE HIGHER THAN NORMAL INDUSTRY STANDARD BURST PRESSURE FOR THE CYLINDER AND HOSE SAFEGUARD THE USER WHEN FIREFIGHTING**
- **LONG LIFE AND LOW MAINTENANCE COSTS ARE ASSURED AS THE EXTINGUISHERS ARE MANUFACTURED FROM A 2 MM THICK STEEL, SHOT BLASTED AND POLYESTER COATED AND WITH AN ANTI-RUST SAFETY PIN**



Higher than industry standard burst pressure

WHEELED FOAM CARTRIDGE

FIRE EXTINGUISHER ↓

TECHNICAL DATA

TECHNICAL DATA		
Capacity	45 L	135 L
Minimum Discharge Range	6 m	6 m
Test Pressure	26 bar	26 bar
Working Pressure	16.4 bar	18.4 bar
Weight Empty	36 kg	96 kg
Weight Full	81 kg	231 kg
Dimensions in Stored Position with Handle, Length x Width x Height	1100 x 500 x 1200 mm	
Hose Length	5 m	5 m
Wheel Diameter	300 mm	400 mm
Fire Rating	A-IVB	A-IVB
Operating Temperature Range	+5 °C to +60 °C	

Instructions For Use


1. Pull out the safety pin
2. Open the tap by fully raising the handle
3. Control the flow rate by squeezing the control valve and direct the spray at the base of the fire

Approvals

These fire extinguishers hold Bureau Veritas EC type examination certificate as per Module B of directive 2014/90/EU of the European Parliament (MED/3.52 Non-portable and transportable fire extinguishers)

These fire extinguishers hold Certificate of type approval from China Classification Society

These extinguishers complies with European standards: EN 1866-1 : 2007 and EN 1866-2 : 2014



Ordering Information

Product Number	Product Name
778998	Wheeled Foam Fire Extinguisher 45 L SE45A2
778996	Wheeled Foam Fire Extinguisher 135 L SE135A2

Accessories

Product Number	Product Name
668210	AFFF Foam Charge for 45 L
668228	AFFF Foam Charge for 135 L
668194	CO ₂ Cylinder 450 g 45 L
735046	CO ₂ Cylinder 900 g 135 L
667683	Safety Pin for All Wheeled extinguishers 10 Pack
667600	Wire and Seal for All extinguishers 90 Pack
667766	O-ring for top 45 L and 135 L