

The Survitec logo features a stylized orange swoosh above the brand name 'survitec' in a white, lowercase, sans-serif font.

FIRE BLANKET

For extinguishing small fires

A flexible 3-ply fire blanket specifically designed to extinguish fire by cutting off the supply of oxygen quickly and efficiently. Our Fire Blanket is suitable for use on small, starting fires, such as galley kitchen fires, and clothing fires.

BENEFITS:

- ✓ **LPCB certified to BS EN 1869:2019**
- ✓ **High-performance protection from the first company in the world to achieve certification to the new standard**
- ✓ **Unique, 3-ply material for extinguishing small, starting fires safely and reliably, and without the mess of a fire extinguisher**
- ✓ **Certified for use on cooking oil fires and flammable liquid fires, and so ideal for use on galley kitchen fires and clothing fires**
- ✓ **Also suitable for use as a heat shield or as wrap-around protection when escaping a fire**
- ✓ **Supplied in a one-piece holder for easy deployment in confined spaces**
- ✓ **5 year guarantee**

**“ Extinguishes small fires
swiftly and effectively ”**



TRUSTED TO
PROTECT LIVES

FIRE BLANKET

TECHNICAL DATA

FIRE BLANKET

Blanket Material	3-ply material comprising two layers of woven glass fibre fabric and an inner layer of fire-retardant film
Handle Material	Flame retardant cotton webbing (Blue)
Weight	1.5 Kg
Dimensions	Fire blanket: 180 cm x 120 cm Holder: 18 (W) x 5(D) x 34(H) cm
Guarantee:	5 Years – Manufacturer recommends replacement after 5 Years
New Standard Requirements	As detailed in BS EN 1869:2019 – The fire blanket must be flexible with good draping qualities to eliminate oxygen from the burning oil and to allow the oil to cool gradually to below its self-ignition temperature. It should not reignite when the blanket is removed after 17 minutes. – The fire blanket must extinguish a flammable fuel fire. To achieve this the fire blanket must be flexible and must eliminate oxygen from the burning fuel. It should not reignite when the blanket is removed after 4 minutes.
Other Information	– Discard after use – Blanket should be withdrawn from holder every 12 months, unfolded, and checked for damage or discolouration of the surface – Check handle fixing every 12 months – Inspection details are on the back label of the Fire Blanket

APPROVALS & ACCREDITATIONS

✓ LPCB certified to BS EN 1869:2019

ORDERING INFORMATION

Code	Product Name
FFBLKT1.8X1.2	Fire Blanket 1.8 x 1.2m EN 1869:2019