



GUARDMAN FIRE HOSE

FIRE FIGHTING HOSE ↓

The Guardman range of hose is specifically designed for marine use providing the user with a long life product suitable for extreme climatic and fire fighting conditions.

FEATURES

- RUGGED WOVEN POLYESTER DESIGN
- LIGHT-WEIGHT
- FITTED WITH STORZ OR NORWEGIAN COUPLINGS
- OUR HOSE IS MADE OF RUBBER BLEND WITH A CIRCULAR WOVEN POLYESTER JACKET GIVING SAFER USAGE OPERATIONS BY ABSORBING SUDDEN PRESSURE INCREASE DURING USE
- LIGHT-WEIGHT DESIGN ENABLES CARRYING THEM WITH EASE ON BOARD A VESSEL WHEN FIGHTING FIRES
- OUR HOSES ARE FITTED WITH EITHER STORZ OR NORWEGIAN STANDARD COUPLING READY FOR VESSEL USE. THE HOSES ARE MADE OF MATERIALS THAT SAFEGUARDS THE HOSES AGAINST EXTERNAL DAMAGE FROM UV RADIATION AND OIL OR COMMONLY USED CHEMICALS



GUARDMAN FIRE HOSE

FIRE FIGHTING HOSE



1 1/2 Inch, 15 M Including Storz C Coupling

TECHNICAL DATA	
Length	15 m
Inner Diameter	1 1/2 inch / 38 mm
Wall Thickness	0.09 inch/2.2 mm
Weight	5.7 kg/3.75 lbs
Max Working Pressure	15 bar
Minimum Burst Pressure	45 bar
Operating Temperature Range	-30 °C to +75 °C
Coupling	
Coupling Size	52=C
Lug Spacing	66 mm
Weight	0.970 kg

Ordering Information

Product Number	Product Name
902859	Guardman 2 inch with Storz C Coupling 20m
902809	Guardman Fire Hose 2 inch, 15 m with Nor-1 Coupling
902813	Guardman Fire Hose 2 inch per m without Coupling
902814	Guardman Fire Hose 2.5 inch per m without Coupling
902809	Guardman Fire Hose 2 inch, 15 m including Nor-2 Coupling
902818	Guardman Fire Hose 1 1/2 inch, 15 m including Storz C Coupling
902810	Guardman Fire Hose 2 inch, 15 m including Storz C Coupling
902821	Guardman Fire Hose 2.5 inch, 15 m including Storz-65 Coupling
902812	Guardman Fire Hose 1.5 inch per m without Coupling
902806	Guardman Fire Hose 2 inch, 15 m without Coupling

Guardman Fire Hose 1 1/2 Inch Without Coupling

TECHNICAL DATA	
Length	Minimum 1 m - Max 2000 m
Inner Diameter	1 1/2 inch/38 mm
Wall Thickness	0.09 inch/2.2 mm
Weight	0.3 kg/m or 0.2 lbs/ft
Max Working Pressure	15 bar
Minimum Burst Pressure	50 bar
Operating Temperature Range	-30 °C to +75 °C

Accessories

Product Number	Product Name
605212	Portable Binding Machine
605220	Clamping Device for Binding Machine
758888	Binding Wire 1.6 mm (1 kg Roll)
605279	Cabinet for 20 m Fire Hose

2 Inch Per M Without Couplings

TECHNICAL DATA	
Length	Minimum 1 m - Max 1000 m
Inner Diameter	2 inch/51 mm
Wall Thickness	0.09 inch/2.2 mm
Weight	0.38 kg/m or 0.25 lbs/ft
Max Working Pressure	15 bar
Minimum Burst Pressure	45 bar
Operating Temperature Range	-30 °C to +75 °C

2 Inch, 15 M Including Storz C Coupling

TECHNICAL DATA	
Length	15 m
Inner Diameter	2 inch/51.5 mm
Wall Thickness	0.09 inch/2.2 mm
Weight	5.7 kg/3.75 lbs
Max Working Pressure	15 bar
Minimum Burst Pressure	45 bar
Operating Temperature Range	-30 °C to +75 °C
Coupling	
Coupling Size	52=C
Lug Spacing	66 mm
Weight	0.970 kg

GUARDMAN FIRE HOSE

FIRE FIGHTING HOSE ↓

2 1/2 Inch, 15 M Complete With Storz-65 Coupling

TECHNICAL DATA	
Length	15 m
Inner Diameter	2 1/2 inch / 65 mm
Wall Thickness	0.09 inch/2.2 mm
Weight	7.95 kg / 5.25 lbs
Max Working Pressure	15 bar
Minimum Burst Pressure	45 bar
Operating Temperature Range	-30 °C to +75 °C
Coupling	
Coupling Size	65=DS
Lug Spacing	81 mm
Weight	1.45 kg

2 1/2 Inch Per M Without Couplings

TECHNICAL DATA	
Length	Minimum 1 m - Max 2000 m
Inner Diameter	2 1/2 inch / 65 mm
Wall Thickness	0.09 inch/2.2 mm
Weight	0.53 kg/m or 0.35 lbs/ft
Max Working Pressure	15 bar
Minimum Burst Pressure	45 bar
Operating Temperature Range	-30 °C to +75 °C

Approvals

SOLAS 74 Convention as amended, Regulation II-2/10,X/3, IMO Res. MSC.36(63)-(1994 HSC Code) as amended, 7, IMO Res. MSC.97(73)-(2000 HSC Code) as amended, 7, EN 14540:2014

SETTING THE GLOBAL STANDARD FOR OVER 160 YEARS

Protecting over 1 million lives across the globe every day, our critical safety and survival solutions help marine, aviation, offshore, and defence personnel get home safely if the worst happens.

Taking responsibility for the entire product lifecycle – from precision engineering and R&D, to manufacturing and servicing – we never compromise when it comes to safety and survival. Committed to protecting lives, we know the small things matter.



GET IN TOUCH

Email info@survitecgroup.com

www.survitecgroup.com

1-5 Beaufort Road, Birkenhead, Merseyside, England CH41 1HQ