

Survitec

# AFFF 3% F-25 PD4344

FOAM CONCENTRATE ↓

Survitec Foam concentrates are either fluoroprotein or synthetic foam types. Depending on application, it can be alcohol resistant for polar. Solvent fi res or regular ones for hydrocarbon fi res. Foam concentrates offered are MED, IMO MSC.1/Circ.1312 approved. Some foam concentrates are HOCNF and ICAO approved.

## FEATURES

- CLASS B FIRES
- FOR FIRES IN HYDROCARBONS
- OUR AFFF 3% F-25 MEETS THE LATEST IMO REGULATIONS MAKING IT IDEAL FOR UPDATING YOUR VESSELS' FOAM FIREFIGHTING SYSTEM
- IDEAL FOR USE FOR YOUR OIL TANKERS AND HELIDECKS' FOAM SYSTEMS
- WHEN STORED CORRECTLY IN ACCORDANCE WITH THE MANUFACTURER'S GUIDELINES OR IN THE CONTAINERS IT IS SUPPLIED IN, IT WILL GENERALLY HAVE A SHELF LIFE IN EXCESS OF 10 YEARS
- GLOBAL AVAILABILITY, FLEET FLEXIBILITY AND STANDARDISATION MAKE IT IDEAL FOR A LONG-TERM SOLUTION



# AFFF 3% F-25 PD4344

FOAM CONCENTRATE ↓

## TECHNICAL DATA

Type	Synthetic AFFF
Usage	Monitors and Portable Applicators
Pump	Centrifugal
Density Kg/L @ 20 °C	1,050 ± 0.02
Viscosity 20 °C mm <sup>2</sup> /s	< 20
Viscosity -25 °C mm <sup>2</sup> /s	<200
pH at 20 °C	6.5 - 8.5
Storage Temperature	-25 to +50 °C
Pour Temperature	-25 °C
Sediments, Maximum (% Vol)	None
Expansion	Low
Expansion Ratio	5-10 times
Drainage Time 25 %/50 %	2-4 / 4-8 min

## Ordering Information

Product Number	Product Name
777692	AFFF F-25 3 % Foam Concentrate 20 L Can
777691	AFFF F-25 3 % Foam Concentrate 200 L Drum

## Approvals

Approved to IMO MSC.1/Circ.1312, MED/3.58.



## FOAMS ON REQUEST

Products		Product	Approvals	Can	Drum	Foam Top-up	Replacement Foam	Can	Drum
AFFF	3%	STHAMEX AFFF 3% F-15 PD4341	MED/ICAO	777686	777685	AFFF 3% F-25 PD4344	AFFF 3% F-25 PD4344	777692	777691



GET IN TOUCH

Email [info@survitecgroup.com](mailto:info@survitecgroup.com)

[www.survitecgroup.com](http://www.survitecgroup.com)

1 - 5 Beaufort Road, Birkenhead, Merseyside, England, CH41 1HQ